

Wood burning heater Harvia Pro 20 LS black

WKPR20LSM

The Harvia 20 LS Pro heater is a popular choice for cottage saunas thanks to its practicality. The left side of the heater features a fixed and easy-to-use 30-litre water tank that heats up the water while the heater is being heated for bathing.

Advantages

- - Harvia Pro 20 LS with a side water tank is a practical wood-burning heater that gives excellent sauna experience
- - Water tank on the left side of the heater, where the water is heated in the spacious 30 litre tank at the same time as the heater heats up the sauna to the desired temperature
- - Easy and safe to use, , the tap for the water tank is located at the front of the heater
- - The front, top and ash box are made of stainless steel, which is easy to keep clean
- - The cast-iron glass hatch adds light and cozy atmosphere to the sauna



Features

Main material : Steel

H x W x D : 760.0 x 580.0 x 510.0 mm

Net weight (kg) : 60.0

Stone amount (kg) : 40.0

| ID | GTIN | Power | Sauna room size min - max m3 |
|-----------|---------------|---------|------------------------------|
| WKPR20LSM | 6417659036566 | 24.1 kW | 8.0-20.0 |

Spare parts

| Product | ID | Pcs |
|--|-------------|-----|
| Casing, Harvia 20 LS | WX059 | 1 |
| Handle and screws, Chrome | SPZKIP-670 | 1 |
| Adjustable legs for LG150/SL | SPZKIP-918 | 1 |
| Nut R1/2 25mm | SPZES-250 | 1 |
| Hinge pin | SPZKIP-50 | 1 |
| Water container, 20 Pro RS/LS | SP520 | 1 |
| Extension 25 mm hot water faucet | SPZES-240 | 1 |
| Connection pipe 200 mm | SPZKIP-130 | 1 |
| Glass 184x210x4 mm Stoves 2006-, transparent | SPZTS-36 | 1 |
| Tab hot water container, Chrome | SPZVS-100 | 1 |
| Gasket for hot water faucet | SPZES-260 | 1 |
| Stove door with glass (from 2006) | SP048 | 1 |
| Cast-iron grating 135x290mm, sauna heaters | SPZKIP-10 | 1 |
| 22LS/RS lid, assembled | SPZROST-619 | 1 |
| Flue pipe connector | SPZROB-200 | 1 |
| Cap for smoke hole (Ø 75 mm) | SPZROB-430 | 1 |
| Ashtray black, sauna heaters | SP682 | 1 |
| Blocking plug with screws | SPZROB-190 | 1 |
| Flue gas heat regulator 2 pcs | SP0009 | 1 |

Technical details

| Technical data | Type / attribute | WKPR20LSM |
|--|--|-----------|
| Technical data | Color | Black |
| | Power output | 24.1 kW |
| | Stone sizes | Ø10–15 cm |
| | Stone amount (kg) | 40 |
| | Dimensions | |
| Dimensions | Product width | 580 |
| | Product height | 760 |
| | Product depth (mm) | 510 |
| | Net weight (kg) | 60 |
| | Gross weight | 63.1 |
| | Package width | 660 |
| | Package height | 760 |
| | Package depth | 550 |
| Connections | Flue connection locations | Back, Top |
| | Chimney connection diameter | 115 |
| Safety and installation dimensions | Safety distance front (non-combustible materials) | 300 |
| | Safety distance front (combustible materials) | 300 |
| | Safety distance right side (combustible materials) | 300 |
| | Safety distance right side non-combustible materials | 100 |
| | Safety distance left side (combustible materials) | 300 |
| | Safety distance left side non-combustible materials | 100 |
| | Safety distance behind (non-combustible materials) | 100 |
| Safety distance behind (combustible materials) | 300 | |

Technical details

| Technical data | Type / attribute | WKPR20LSM |
|----------------|--|-----------|
| | Safety distance (Ceiling) | 1300 |
| | Room min. height(depends on connections and therefore from output, star/delta) | 2060 |